



# REFEX™ 2001 Series 3/4" and 1" pH Combination Electrodes

Maintenance free REFEX™ 2001 Series electrodes are designed for pH measurement in rugged applications. 2001 Series combination electrodes feature the patented Refex non-porous, hard ionically conductive interface/barrier to prevent reference electrode electrolyte loss and poisoning.

Typical application areas: Petro/Chemical, Pulp & Paper, Water Treatment, UPW

## Specifications:

Measuring Method:	pH / reference combination electrode
Reference Junction / Half Cell:	Patented non-porous Refex interface. Ag/AgCl in KCl 2.8 mol/l (sealed for life)
Range:	pH 0...12
Eo Zero vs Ag/AgCl:	pH = 6.8 (+/- 20 mV)
Impedance pH-glass/ref:	200 MΩ Nom. / <100 kΩ
Temperature Range:	0...100°C
Pressure Range:	0...20 bar
Liquid Earth:	Optional 316 SS LE available
Temperature Sensor:	Optional 100Ω/1000Ω RTD
Standard Dimensions:	3/4" and 1" NPT threaded bodies
Electrode Body Material:	PVDF standard; Triton optional
Electrical Connector:	Cable 1m, 5m, 10m, others
Recommended Storage:	Hydrate in 2.8 mol/l KCl, ambient temp.



3/4"-2001-PT100-LE

1"-2001-PT100-LE



## **Applications: In-Line and Immersion Systems**

- Potable Water Applications
- Optimized Coagulation
- Low Ionic Raw Water and Ultra Pure Water (UPW)
- All Oil & Gas Sour Water
- All Petrochemical Process Water
- Chlor-Alkali - Chlorinated and Waste Brines
- Food and Beverage - CIP and SIP
- Industrial Waste Water
- Waste Water Treatment
- Heavy Metal Processes
- Pulp and Paper

## **Advantages of Reflex Non Porous Electrodes**

- Protected Ag/AgCl reference half cell - REFEX barrier/interface prevents all liquid contact/exchange
- Resistant to fouling and poisoning
- Suitable for temperatures between 0...100°C
- Operates in pressures between full vacuum and 20 bar / 290 psi
- Instantaneous response to pH change
- Constant Eo zero - almost maintenance free
- Long electrode life - many times longer than all others
- Compatible with all modern pH instruments with dual high impedance inputs for pH and reference electrodes.
- No diffusion potential errors in low ionic waters
- No electrolyte refilling - sealed for life

For more information:  
[www.southforkinst.com](http://www.southforkinst.com)  
[info@southforkinst.com](mailto:info@southforkinst.com)  
T: 925-461-5059

