

# In-line Filtration

## Advantages

- **Long filter endurance**  
Up to now over 3 years
- **Low Maintenance**  
No continuous maintenance necessary
- **Low running costs**  
No tube changes, no chemicals
- **Easy cleaning**  
Normally every 2 to 6 weeks  
Raise it, wipe it, reinsert it!  
It takes only 1 minute
- **Weight**  
4 kg Easy to handle

## Technical Data

- Low-maintenance filter 350 x 450 mm
- Filtrate flow: max. 1000 ml/h adjustable
- Ready mounted on a steel mounting place (1.4571)
- Distance from analyzer: max. 100 m
- Control unit ready mounted in a glass-fibre cabinet
- Membrane pump, manometer, SPS and terminal box included
- Special filters for UV and chemical resistance
- Heated sample line with thermostat
- Power supply  
230 V / 50 Hz, 20 W

More than 3 years of practical experience with the easiest and lightest filtration.



In North America:



[www.southforkinstruments.com](http://www.southforkinstruments.com)

---

**SPX**<sup>®</sup>

SPX Flow Technology Norderstedt GmbH - Werkstraße 4 - D-22844 Norderstedt  
Phone: +49 40 52202-0 Fax: +49 40 52202-444 E-Mail: [branluebbe@spx.com](mailto:branluebbe@spx.com)

SPX reserves the right to incorporate our latest design and material changes without notice or obligations.

Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region. For more information visit [www.spx.com](http://www.spx.com).

"The green ">" is a trademark of SPX Corporation, Inc."