




EXmatic 471 electro pneumatic - programmable




- >> Full automatic measuring points
- High extension of sensor-lifetime and reducing of servicing efforts
- Open system operates with any kind of transmitter
- Output signals for connecting with PCS
- >> Three different cleaning solutions usable
- Sealing water function
- Pre- and post-cleaning function

EXmatic 471 is an electro-pneumatic control unit for fully automatic control of 2 pneumatic retractable probe housings of EXtract 8XX series. It allows a "plug and play" installation and individual programming.

Specifications

Voltage supply:	24 V DC / 30 VA					
Air supply:	compressed air 6 bar					
Input for ext. trigger:	24 V DC internal power					
	supply for potentialfree					
	contact					
Current consumption:	1,6 A max.					
Output ext. relays:	24 V DC max. 250 mA					
Output pump:	24 V DC max. 250 mA					
Output alarm contacts:	24 V DC max. 100 mA					
Housing material:	glass-reinforced plastic or stainless steel					
Housing dimensions:	300 x 400 x 200 mm					
Ambient temperature:	0+55 °C					
Type of protection:	IP54					


Dimensions



Contact:




Tel: 925 461 5059





EXmatic 471 electro pneumatic - programmable









Measuring point with probe housings, flow-through fittings and control unit

Order code

C 1				D !: .:
Code	_		Housing	Delivery time
GF1 Plastic hou			Plastic housing with Display	4 Weeks
SS1			Stainless steel housing with Display	4 Weeks
	Code	е	Cleaning probe housing 1 / probe housing 2	Delivery time
	11		for 1 cleaning solution / for 1 cleaning solution	3 Weeks
	12		for 1 cleaning solution / for 2 cleaning solutions	3 Weeks
	13		for 1 cleaning solution / for 3 cleaning solutions	3 Weeks
	22		for 2 cleaning solutions / for 2 cleaning solutions	3 Weeks
	23		for 2 cleaning solutions / for 3 cleaning solutions	3 Weeks
	33		for 3 cleaning solutions / for 3 cleaning solutions	3 Weeks
		Code	Length of connecting hose probe housing 1 / probe housing 2	Delivery time
		0000	without / without	3 Weeks
		0003	without / 3 meters	3 Weeks
		0005	without / 5 meters	3 Weeks
		0010	without / 10 meters	3 Weeks
		0303	3 meters / 3 meters	3 Weeks
		0305	3 meters / 5 meters	3 Weeks
		0310	3 meters / 10 meters	3 Weeks
		0505	5 meters / 5 meters	3 Weeks
		0510	5 meters / 10 meters	3 Weeks
		1010	10 meters / 10 meters	3 Weeks
		Со	ode Interface	Delivery time
		EN	l without	3 Weeks