KENTRAK (

DCP007-UV Industrial Photometer



FEATURES

- Dual wavelength UV-VIS-NIR absorption
- Low power mercury free UV LED light
- Zero dead volume hygienic cells
- Traditional & single use technology
- Verification accessory (NIST traceable)
- Light source & wavelength easy to change
- Alarm, 4-20 mA and Modbus TCP communications



The Kemtrak DCP007-UV process analyzer is a high performance fiber optic coupled photometer for high resolution, real time, inline concentration measurement.

The Kemtrak DCP007-UV can be deployed in both fixed installations and with single use technology. Kemtrak analyzers provide deep absorbance measurements (up to OD 200) and do not require calibration for absorption measurement.

For protein detection and fractionation, the DCP007-UV uses cold, low power, UV light sources to prevent heat shocked protein (HSP) issues and minimize product loss through denaturing. Environmentally friendly, mercury-free LED light source technology assures drift-free operation with exceptionally high precision.

Kemtrak industrial-grade hygienic measurement cells with scratch-resistant sapphire windows contain no electronics or moving parts, making them ideal for both ordinary and hazardous area use. Standard NIST-traceable verification filters are used to verify analyzer performance without process interruption. Standard features include 16 separate linearization/calibration tables for multiple product operation, remote zeroing, automatic cleaning cycle operation and advanced signal filtering. An on-board graphical internet based configuration utility allows remote operation, calibration, validation, and data trending using a standard PC.

All Kemtrak products are designed to meet the most demanding application specifications and are made from the highest quality materials to ensure exceptionally long life and the highest reliability.

TYPICAL APPLICATIONS:

- Protein / API detection and concentration
- Chromatographic fractionation
- Leak, carryover & interface detection
- Filtration monitoring and centrifuge / separator control
- Chemical concentration
 - chlorine, hydrogen peroxide
 - aromatics & hydrocarbons
- DOC, COD and TOC (SAC 254)



KENTRAK

DCP007-UV Industrial Photometer

TECHNICAL DATA

HOUSING

Stainless steel EN 1.4301 (X5CrNi18-10), AISI 304 (V2A) Cam lock with double bit insert & external mounting brackets 224 x 215 x 125 mm (L x W x D) IP 65 / FN 60529

DISPLAY

 16 x 4 alphanumeric white on blue dot matrix LCD display

 LED background illuminated

 Measurement updates every second

 LED 1 (green):
 Power on

 LED 2 (red):
 System fault

 LED 3 & 4 (orange):
 Alarm 1 & Alarm 2

 LED 5 (blue):
 Clean / Hold

OPERATION

Menu based with 4 operator buttons Remote HTML/Java interface (TCP/IP connection via Ethernet port)

SOFTWARE FEATURES

Auto gain:	Fully automatic signal gain controller
Auto zero:	Automatically, locally or remotely activated zero
Calibration:	16 linearization tables for concentration & mA output
Damping:	From 0 to 9999s with noise (air bubble / particle) filter
Memory:	Nonvolatile - all data retained upon power failure
Security:	Alphanumeric password protection

DATA LOGGER

>17000 data points (timestamp, average, max. & min.), ring buffer Configurable log time interval 1 s to 24 hr

EVENT LOGGER

>16000 events, ring buffer Timestamp, alarms, zeroing, cleaning, product change, calibration & system events (power, system warning & error messages)

AUTOMATIC CLEANING CONTROL

Automatic cleaning sequence, triggering dedicated relay output Manual trigger or external trigger via digital input Configurable automatic cleaning interval, 15 min to 2 months Configurable cleaning duration from 0 to 9999 s Auto-zero after clean option Hold value during clean 0 to 9999 s Hold value after clean (to equilibrate) 0 to 9999 s

PID CONTROLLER

Control method: Pulse width modulated relay output or0/4-20mA outputControl period:2 - 99 sProportional gain:0.0000 - 999999Integral time:0.0000 - 999999 sDerivative time:0.0000 - 999999 s

REMOTE INPUT

 5 x Digital input (potential free contact) for:

 Input 1-3:
 Product/range selection

 Input 4:
 Zero, instant zero, clean or clean & Zero

 Input 5:
 Hold (freeze output), data log or light source control

ANALOGUE INPUT (OPTION)

mA or 3-wire PT100 Range: -20 to 200 °C (-4 to 392 °F) Resolution: 0.07 °C (0.126 °F)

LIGHT SOURCE

High performance light emitting diode (LED) Wavelength range: 250 - 1050 nm Full Width-Half Maximum (FWHM): 10 nm Central Wavelength (CWL) Accuracy: ±1 nm Typical lifetime: > 2000 hrs @ 280 nm >100000 hrs @ 500 nm

PHOTOMETRIC RANGE

0.000 - 4.5 AU @ 280 nm, 10 mm OPL 0.000 - 5.0 AU @ 500 nm, 10 mm OPL

PHOTOMETRIC ACCURACY ±0.001 AU at 1 AU

PHOTOMETRIC NOISE

±0.0001 AU at 1 AU

LINEARITY

± 0.5 % of respective measuring range

mA OUTPUT

1 x selectable 0 - 20 mA / 4 - 20 mA NAMUR NE43 compliant Galvanically isolated, 500 VDC Accuracy: <0.1 % Resolution: 0.025 % Load: 0 - 600 Ohm Optional second mA output

RELAY OUTPUTS

1 x 1 A 240 VAC Failsafe output (active when system is ok) 2 x 1 A 240 VAC User configurable (alarm, PID) 1 x 1 A 240 VAC Automatic cleaning control Fuses: 4 x 1 A (type: MXT), max 100 A breaking capacity LED status indicators flash when relays are active

FAIL-SAFE

Dedicated relay output, 1A 240 VAC mA output value used to signal a system fault mA outputs compliant to NAMUR NE43

NETWORK INTERFACE (REMOTE COMMUNICATIONS)

TCP/IP, 10Base-T and 100Base-TX Link Connector: RJ45 Protocol:

- 1. HTML interface using native protocol over TCP/IP
- Java® version 8 update 202 or later required 2. MODBUS slave over TCP/IP (V1.1b3 compliant)
- Functions: (0x03, 0x04, 0x2B/0x0E conformity 0x01)

OPERATING CONDITIONS

 Ambient temperature:
 0 °C to +50 °C (32 °F to 122 °F)

 Transport:
 -20 °C to +70 °C (-4 °F to 158 °F)

POWER SUPPLY

100-240 VAC, 50-60 Hz & 22 - 30 VAC/VDC Mains fuse: 1 A (type MST), Max breaking capacity 35 A

POWER CONSUMPTION 25 VA (max.)

CERTIFICATES

Kemtrak AB • SE 187 66 Stockholm • Sweden sales@kemtrak.com • www.kemtrak.com

We reserve the right to make changes without prior notice



e: sales@southforkinstruments.com t: +1 (925) 461-5059 w: www.southforkinstruments.com

PROCESS MEASUREMENT CELL

PROCESS CONNECTION

Standard designs include DIN Flange (DIN 2633), ANSI (ASME B16.5), Tri-Clamp® (ISO 2852 & DIN 32676), Straight pipe thread (DIN ISO 228 BSP), NPT tapered pipe thread (ANSI B 1.20.1), single use barbed hose. Line size up to DN200 / 8".

MATERIALS

Wetted surfaces in stainless steel EN 1.4435 or EN 1.4404 (316L). Other materials include Titanium Gr 2, Hastelloy C-276 & C-22, Monel 400 & PTFE C25 (TFMC, carbon filled Teflon®), PPSU.

WINDOW

Sapphire, UV fused silica.

SURFACE FINISH

Fine machine (smooth). Ra <0.38 μm (electropolished) wetted surfaces on hygienic measurement cells.

ELASTOMERS

FPM (FKM/Viton®, FDA), FFKM (Chemraz®/ Kalrez®, FDA), EPDM (FDA).

OPERATING CONDITIONS

Ambient & process temperatures up to $275 \,^{\circ}$ C ($527 \,^{\circ}$ F). Process pressure from 10 mbar to 200 bar ($0,14 - 2900 \,$ psi). Operating conditions subject to material and design in use. Higher pressures & temperatures on request.

FIBER OPTIC CABLE

Silica core photonic fiber with Kevlar® reinforced flexible LZSH coated stainless steel jacket. Fully-interlocked stainless steel conduit for use above 85 °C (185 °F). Terminated with SMA 905 connectors. Lengths up to 100 m (328 foot).

PROTECTION

IP66 / EN 60529

Kemtrak is the leading manufacturer of high performance LED based industrial photometers and automation products for the process engineering industry.

Kemtrak provides tailor made solutions to meet the needs of a wide range of industries including chemical, petrochemical & offshore, biotech, pharmaceutical, food & beverage, pulp and paper and water & environment.

Kemtrak has trained representatives and support personnel globally and is certified according to ISO 9001:2015.